

Sangoma Handsets Default login

164 Jonathan Thu, Oct 5, 2017 [How to and FAQs](#) 9138

The default login details for a default Sangoma handset is;

Username: admin

Password: admin

This should be the default password for handsets out of the box or after a factory reset, please note that these handsets support zero touch and if purchased via us they will most likely upon first boot or reset just connect directly to your PBX and the password will change to your PBX systems password. This will be the password you have specified for handset admin and user access see steps below;

The screenshot displays the Sangoma Admin web interface. At the top, there is a navigation bar with tabs: 'Modules', 'Basic Mode', 'Dashboard', and 'UCP'. Below this, a sidebar menu lists various administrative functions. The main content area shows a grid of links categorized by function. In the 'Settings' section, 'Endpoint Manager' is highlighted with a red circle. Below the main grid, the 'Endpoint Manager' module is expanded, showing a description and a sub-menu. In the sub-menu, 'Global Settings' is highlighted with a red circle.

Admin	REST API	Follow Me	DAHDI Channel DIDs	Weak Password Detection
Administrators	RMS Management	IVR	DAHDI Config	Settings
Asterisk CLI	Sound Languages	Languages	Firewall	Advanced Settings
Asterisk Modules	System Admin	Misc Applications	Inbound Routes	Asterisk IAX Settings
<u>Backup & Restore</u>	System Recordings	Misc Destinations	Outbound Call Limit	Asterisk Logfile Settings
Blacklist	User Management	Paging and Intercom	Outbound Routes	Asterisk Manager Users
Bria Cloud Solutions	XMPP	Park and Announce	SIPSTATION	Asterisk REST Interface Users
Bulk Handler	XactViewV3 Admin	Parking	Trunks	Asterisk SIP Settings
CID Superfecta	Zulu	Queue Callback	Reports	CRM Settings
CallerID Lookup Sources	Applications	Queue Priorities	Asterisk Info	<u>EndPoint Manager</u>
Certificate Management	Announcements	Queues	Asterisk Logfiles	Pbx Configuration

Endpoint Manager

About Endpoint Manager

This module is used to automatically provision & configure Desk Phones, Wireless Phones, Door Phones, Overhead Paging Devices, Gateways, and Specialty devices from supported manufacturers.

For information and instructions on using Endpoint Manager, please see the Endpoint Manager Wiki .

To get started please choose an option in the Menu on the right.

EndPoint

- Global Settings
- Extension Mapping

Brands

Then in the next screen add your desired passwords that your handsets will be set to;

Endpoint Manager

Global Settings

Internal Address ⓘ

External Address ⓘ

Ports ⓘ

HTTP Provisioning Port	<input type="text"/>	Firewall Zone(s): Internal, Other
Secure HTTPS Provisioning Port	<input type="text"/>	Firewall Zone(s): Internal, Other
RESTfull Apps Port	<input type="text"/>	Firewall Zone(s): Internal
Secure RESTfull Apps Port	<input type="text"/>	Firewall Zone(s): Internal

Authentication of HTTP or HTTPS provisioning requests from endpoints is currently **enabled**. Configuration of provisioning ports and credentials is done through Sysadmin Provisioning Management .

The username that is currently configured for HTTP and HTTPS provisioning is '

Phone User Password ⓘ

ReSync Time ⓘ
Seco

XML-API (RestAPI) Default Login ⓘ

Yes
No

Extension Mapping IP Addresses ⓘ

Yes
No

Extension Mapping Phone Status ⓘ

Yes
No

Value Correction ⓘ

Yes
No

Admin UCP for All ⓘ

Yes
No

> Save Global

Online URL: <https://kb2.ic.uk/article.php?id=164>