

Sangoma Handsets Default login

164 Jonathan Thu, Oct 5, 2017 [How to and FAQs](#) 8951

The default login details for a default Sangoma handset is;

Username: admin

Password: admin

This should be the default password for handsets out of the box or after a factory reset, please note that these handsets support zero touch and if purchased via us they will most likely upon first boot or reset just connect directly to your PBX and the password will change to your PBX systems password. This will be the password you have specified for handset admin and user access see steps below;

The screenshot displays the Sangoma Admin web interface. At the top, there is a navigation bar with tabs for 'Modules', 'Basic Mode', 'Dashboard', and 'UCP'. Below this, a sidebar menu on the left lists various administrative functions such as 'Admin', 'Backup & Restore', 'Blacklist', 'Bria Cloud Solutions', 'Bulk Handler', 'CID Superfecta', 'CallerID Lookup Sources', and 'Certificate Management'. The main content area is divided into several columns of links. The rightmost column, under the heading 'Settings', contains links for 'Advanced Settings', 'Asterisk IAX Settings', 'Asterisk Logfile Settings', 'Asterisk Manager Users', 'Asterisk REST Interface Users', 'Asterisk SIP Settings', 'CRM Settings', 'EndPoint Manager', and 'Fax Configuration'. The 'EndPoint Manager' link is highlighted with a red circle. Below the main menu, the 'EndPoint Manager' section is expanded, showing a description of the module and a sub-menu on the right. The sub-menu includes 'EndPoint', 'Global Settings' (highlighted with a red circle), 'Extension Mapping', and 'Brands'.

Then in the next screen add your desired passwords that your handsets will be set to;

Endpoint Manager

Global Settings

Internal Address ⓘ

External Address ⓘ

pbxXXXXXXXXX.ic-talk.co.uk

Ports ⓘ

HTTP Provisioning Port		Firewall Zone(s): Internal, Other
Secure HTTPS Provisioning Port		Firewall Zone(s): Internal, Other
RESTfull Apps Port		Firewall Zone(s): Internal
Secure RESTfull Apps Port		Firewall Zone(s): Internal

Authentication of HTTP or HTTPS provisioning requests from endpoints is currently **enabled**. Configuration of provisioning ports and credentials is done through Sysadmin Provisioning Management .

The username that is currently configured for HTTP and HTTPS provisioning is 'XXXXXXXXXX' and the password is 'XXXXXXXXXX' (without quotes).

Phone Admin Password ⓘ

123456

Phone User Password ⓘ

7890

ReSync Time ⓘ

86400

Seco

XML-API (RestAPI) Default Login ⓘ

Yes

No

Extension Mapping IP Addresses ⓘ

Yes

No

Extension Mapping Phone Status ⓘ

Yes

No

Value Correction ⓘ

Yes

No

Admin UCP for All ⓘ

Yes

No

Save Global

Online URL: <https://kb2.ic.uk/article.php?id=164>