

# call barge in to specific DDI's using chanspy

204 Keira Tait Fri, Apr 27, 2018 [Sangoma PBXact](#) 1643

In order to setup call barge in, you will need to follow the below steps

First, enable chanspy in modules > feature codes, and then select the extension you want.



Then go to modules > config edit, you are looking for extensions\_custom.conf

**+ Add New File**

The screenshot shows a file tree interface for managing Asterisk configuration files. The root folder is 'Asterisk Custom Configuration Files'. Inside, there are several subfiles listed:

- ari\_additional\_custom.conf
- ari\_general\_custom.conf
- ccss\_general\_custom.conf
- cel\_custom\_post.conf
- cel\_general\_custom.conf
- cel\_odbc\_custom.conf
- confbridge\_custom.conf
- extensions\_custom.conf** (highlighted)
- extensions\_custom\_asternic\_outbound\_freepbx.conf
- extensions\_custom\_asternic\_outbound\_freepbx\_failover.conf
- features\_applicationmap\_custom.conf
- features\_featuremap\_custom.conf
- features\_general\_custom.conf
- freepbx\_menu.conf
- freepbx\_module\_admin.conf
- globals\_custom.conf
- http\_custom.conf
- iax\_custom.conf

If you go into this file, you want to paste the below code and remove or add what you want in order to block barge in on particular ddi's.

```
[ext-local-custom]
; Block Access
exten => _*2227760,1,Macro(user-callerid,)
```

```
exten => *_2227760,n,Hangup
exten => *_2237760,1,Macro(user-callerid,)
exten => *_2237760,n,Hangup
exten => *_2247760,1,Macro(user-callerid,)
exten => *_2247760,n,Hangup
exten => *_2227761,1,Macro(user-callerid,)
exten => *_2227761,n,Hangup
exten => *_2237761,1,Macro(user-callerid,)
exten => *_2237761,n,Hangup
exten => *_2247761,1,Macro(user-callerid,)
exten => *_2247761,n,Hangup
exten => *_2227721,1,Macro(user-callerid,)
exten => *_2227721,n,Hangup
exten => *_2237721,1,Macro(user-callerid,)
exten => *_2237721,n,Hangup
exten => *_2247721,1,Macro(user-callerid,)
exten => *_2247721,n,Hangup
; Listen
exten => *_222x.#,1,Macro(user-callerid,)
exten => *_222x.#,n,Answer
exten => *_222x.#,n,NoCDR
exten => *_222x.#,n,Wait(1)
exten => *_222x.#,n,ChanSpy(sip/${EXTEN:4},q)
exten => *_222x.#,n,Hangup

; Whisper
exten => *_223x.#,1,Macro(user-callerid,)
exten => *_223x.#,n,Answer
exten => *_223x.#,n,NoCDR
exten => *_223x.#,n,Wait(1)
exten => *_223x.#,n,ChanSpy(sip/${EXTEN:4},qw)
exten => *_223x.#,n,Hangup

; Barge In
exten => *_224x.#,1,Macro(user-callerid,)
exten => *_224x.#,n,Answer
exten => *_224x.#,n,NoCDR
exten => *_224x.#,n,Wait(1)
exten => *_224x.#,n,ChanSpy(SIP/${EXTEN:4},qB)
```

```
exten => *_224x.#,n,Hangup
```

Note you want to change the \*222, \*222, \*223 and \*224 to the code you wish to dial when doing the barge in.

Online URL: <https://kb2.ic.uk/article.php?id=204>